



MODEL: IC-12V60-EP4S

Lithium Ion Deep Cycle Battery

ELECTRICAL SPECIFICATIONS

Nominal Voltage	12.8V
Nominal Capacity	60Ah
Capacity @ 25A	60Ah
Energy	768Wh
Resistance	< 30mΩ
Efficiency	99%
Self Discharge	≤3%/month
Maximum Modules in Series	4S

DISCHARGE SPECIFICATIONS

Maximum Continuous Discharge Current	60A
Peak Discharge Current	170A/3s
BMS Discharge Current Cut-C	60A
Recommended Low Voltage Cut-Off	11V
BMS Discharge Voltage Cut-Off	10.6~11V
Reconnect Voltage	12V
Short Circuit Protection	660A/500uS

TEMPERATURE SPECIFICATIONS

Discharge Temperature	-20 ~ 60°C
Charge Temperature	0~45°C
Storage Temperature	0°C<T<30°C
BMS High Temperature Cut-Off	60°C
Reconnect Temperature	45°C

MECHANICAL SPECIFICATIONS

Dimensions (Lx W x H)	205*180*190(±3mm)
Weight	7.5±0.5kg
Terminal Type	UNC-M6
Terminal Torque	6N*m
Case Material	ABS+PC
Enclosure Protection	IP67
Cell Type - Chemistry	LFP

CHARGE SPECIFICATIONS

Recommended Charge Current	30A
Maximum Charge Current	60A
Recommended Charge Voltage	14.6V
BMS Charge Voltage Cut-Off	15V
Reconnect Voltage	13.8V

COMPLIANCE SPECIFICATIONS

Certifications	CE,UN38.8
----------------	-----------

FEATURES

BlueTooth APP



Monitor your battery's vitals straight from your smartphone.

Distributed by: 

lithiumhub.com